

技术参数

硅橡胶涂层玻璃纤维套管

阻燃
2R-SG

P. LEO & CO LTD

P.O. Box 175 Fo Tan, Shatin, Hong Kong.
Telephone : (852) 2604-8222 * Facsimile : (852) 2693-2093
E-mail : sales@pleo.com * Web Site : http://www.pleo.com



UL FILE #E195829

硅橡胶涂层玻璃纤维套管

UL Cat. No. 2R-SG, 2R-SG-1, 2R-SG-2, 2R-SG-3

描述: 硅橡胶涂层玻璃纤维套管, 具有出色的热保护性能和弹性; UL 认可文件号 E195829. 用于 UZIQ2 类别的 UL 基本标准是 ANSI/UL1441 和成功经过用导线支撑的耐燃测试并有“VW-1”标识的软管。

电气绝缘套管应用于:

- 高温 & 低温应用程序
- 高电压 & 低电压用用程序
- 耐磨 & 其他对机械性要求高的应用程序
- 阻燃性
- UL 要求
- 与聚酯、丙烯酸、环氧基树脂、酚醛树脂 & 其他线珐琅兼容。

UL Cat. No.	描述	耐热性(°C)	内径(mm)	击穿电压	长度
2R-SG-1 2R-SG-2 2R-SG-3	硅橡胶涂层玻璃纤维套管 “ - ”	200	1 to 10	>3000V >2500V >1500V	1 Meter or Roll

内径 (mm)		壁厚 (mm)
标准	公差	
1~3.5	+0.30/-0.10	0.50
4~10	+0.50/-0.30	0.70

P. LEO

® Pbobbin ® BCwire ® BCmica ® BCtube ® is P. Leo & Co., Ltd. registered trade mark

Important Notice to Purchase

All Statements, technical information and recommendations contained herein are based on tests we believe to be reliable, but the accuracy or completeness thereof is not guaranteed and the following is made in lieu of all warranties, express or implied: Seller's and manufacturer's only obligation shall be to replace such quantity of the product of the product proved to be defective. Neither seller nor manufacturer shall be liable for any injury loss or damage direct or consequential arising out of the use of or the inability to use the product. Before using users shall determine the suitability of the product for their intended uses and users assume all risk and liability whatsoever in connection therewith.

No statement or recommendation not contained herein shall have any force or effect unless in an agreement signed by officers of Seller and manufacturer.